CS-CV228-A0-3C2WFR C4W 1080P Outdoor Smart Wi-Fi Camera




Introduction

EZVIZ products have been designed for your entertainment, communication and security. When you install the EZVIZ APP on your smartphone or tablet, EZVIZ devices will be connected to the cloud via their QR code and will immediately be online. With EZVIZ you can talk to your loved ones, watch your child's progress when you are away, keep an eye on your home, interact with your four-legged friends and prevent household accidents.

Main Features

H.265	H.265 Video Technology	Ϋ́	Active Defense with Siren and Strobe light
Ŕ	Motion Detection	A°	User Defined Alarm Tones
Q;	Two-way Talk	(((•)))	Wi-Fi 2.4GHz Built-in Dual Wi-Fi Antennas
67	Dustproof and Waterproof IP67		MicroSD Slot for Local Storage (Up to 256GB)

Dimension





Specifications

Model	CS-CV228-A0-3C2WFR			
Camera				
Image sensor	1/2. 7" Progressive Scan CMOS			
Shutter Speed	Self-adaptive shutter			
Lens	2.8mm, view angle: 103° (Horizontal), 118°(Diagonal) 4mm, view angle: 87° (Horizontal), 104°(Diagonal)			
Lens Mount	M12			
Day & Night	IR-cut filter with auto-switching			
DNR	3D DNR			
WDR	Digital WDR			
Compression				
Video Compression	H.264/H.265			
Video Bit Rate	Ultra-HD; HD; Standard. Adaptive bit rate.			
Image				
Max. Resolution	1920 × 1080			
Frame Rate	Max: 30fps; Self-Adaptive during network transmission			
Network				
Smart Alarm	Motion detection, Active sound and light alarm			
User Defined Alarm Tone	Supports			
Wi-Fi Pairing	AP paring			
Protocol	EZVIZ cloud proprietary protocol			
Interface Protocol	EZVIZ cloud proprietary protocol			
Interface				
Storage	Micro SD card slot (Max. 256G)			
Wired Network	RJ45 X 1 (10M/100M self-adaptive Ethernet port)			
Wi-Fi				
Standard	IEEE802.11b, 802.11g, 802.11n			
Frequency Range	2.4 GHz ~ 2.4835 GHz			
Channel Bandwidth	Supports 20MHz			
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK			
Transmission Rate	11b: 11Mbps, 11g :54Mbps, 11n :144Mbps			
General	20° C to $(22^{\circ}$ C to 140° C) there is the 00° c to $(22^{\circ}$ c to $(22^{\circ}$ c to (22°) c to (22°)			
Operating Conditions Power Supply	-30°C to 60°C (-22°F to 140 °F), Humidity 95% or less (non-condensing) DC 12V/1A			
Power Consumption	6W max			
IR Range	MAX. 30 meters(98.43ft)			
IP Grade				
Dimensions	Max Diameter: 105mm(4.13"); Height: 95mm(3.74")			
Packaging Dimensions	147mm x 145mm x 173mm (5.79" x 5.71" x 6.81")			
Bare Weight	330g(0.73lb)			

