

RF Power Divider

Electrical Specifications

| | |
|-------------------------------|---------------------|
| Frequency Band | 30-700 MHz |
| Input Power (Max.) | 0.5 W (as splitter) |
| Insertion Loss (Max. / Typ.) | 9.5 / 9.2 dB |
| Isolation Port-to-Port (Min.) | 23 dB |
| VSWR (Max.) | 1.5:1 |
| Impedance (Nom.) | 50 Ω |
| RF Connectors | BNC Female |

Mechanical Specifications

| | |
|----------------------|--|
| Finish | Yellow Chem Film |
| Overall Size (HxWxD) | 1" x 6.75" x 5.3" (25 x 171 x 135 mm) |
| Net Weight | 0.6 lbs (0.3 kg) |
| Ship Weight | 2 lbs (0.9 kg) |

Environmental Specifications

| | |
|-----------------------|-------------------------------|
| Operating Temp. Range | -22 to 140 °F (-30 to +60 °C) |
|-----------------------|-------------------------------|



EMR Power Dividers offer frequency ranges from 30 MHz to 960 MHz with low insertion loss and excellent VSWR. All EMR power dividers are backed by 5-Year Warranty and manufactured in the USA.

Product Features

- Wideband
- High isolation
- Low loss
- 5-Year warranty

