

AUDACIOUS® Premium Audio

Part Number: 5473

Description 16 AWG 2C AUDACIOUS Premium Audio CMR/CL3R FT4
Specifications UL Standards 13 & 444; NEC Articles 725 & 800; CSA C22.2 NO. 214

Construction

Conductor

Type 16 AWG 65/34 Stranded Oxygen-Free Bare Copper

Insulation

Type PVC
Thickness 0.015" nom.
Colors Black, Red
Diameter 0.086" nom.
Lay Length 3.50" nom.
Rip Cord Yes

Jacket

Type PVC
Thickness 0.035" nom.
Outer Diameter 0.262" nom.
Color White or Violet

Print Legend HONEYWELL AUDACIOUS OXYGEN FREE P/N 5473 2C16 E175106 (UL) CL3R OR
CMR C(UL)US FT4 75C SUN RES (RoHS) W/O#XXXXXX-XXXXXX XXXXX FT - L C R
LR RR RM# A B C D E F 1 2 3 4 5 6 7 8 9 (PAT PEND)

Packaging

500' Reel-in-a-Box

Ratings

Temperature -20°C to 75°C
Voltage 300V max.
Capacitance 22pF/ft. nom.
Impedance 85 Ohms nom.
DC Resistance 4.10 Ohms/1000ft. at 20°C
Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)