

AUDACIOUS® Premium Audio

Part Number: 5475

Description 14 AWG 2C AUDACIOUS Premium Audio CMR/CL3R FT4
Specifications UL Standards 13 & 444; NEC Articles 725 & 800; CSA C22.2 NO. 214

Construction

Conductor

Type 14 AWG 105/34 Stranded Oxygen-Free Bare Copper

Insulation

Type PVC
Thickness 0.015" nom.
Colors Black, Red
Diameter 0.105" nom.
Lay Length 4.25" nom.
Rip Cord Yes

Jacket

Type PVC
Thickness 0.035" nom.
Outer Diameter 0.306" nom.
Color White or Neon Green

Print Legend HONEYWELL AUDACIOUS OXYGEN FREE P/N 5475 2C14 E175106 (UL) CL3R OR CMR C(UL)US FT4 75C SUN RES (RoHS) W/O#XXXXXX-XXXXXX XXXXX FT - L C R LR RR RM# A B C D E F 1 2 3 4 5 6 7 8 9 (PAT PEND)

Packaging

500' Reel, Pull Box, or Reel-in-a-Box

Ratings

Temperature -20°C to 75°C
Capacitance 25pF/ft. nom.
Impedance 75 Ohms nom.
DC Resistance 2.60 Ohms/1000ft. at 20°C
Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)