

# B50-TURBO-ZW

## 5 MP Bullet Camera



### Key features

5 MP high performance COMS.

2560 X 1944 resolution.

2.7 mm to 13.5 mm motorized vari-focal lens.


EXIR 2.0, smart IR, up to 40 m IR distance.

OSD menu, 2D DNR, DWDR.

4 in 1 video output (switchable TVI/AHD/CVI/CVBS).

IP67.

Up the coax (HIKVISION-C).



**epcom**

Camera	
Image Sensor	5 MP CMOS image sensor
Effective Pixels	2560 (H) x 1944 (V)
Min. illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Lens	2.7 mm to 13.5 mm motorized vari-focal lens
Horizontal Field of View	95.7° to 29.1°
Lens Mount	Φ 14
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°; Tilt: 0° to 90°; Rotate: 0° to 360°
Synchronization	Internal synchronization
Frame Rate	PAL: 5 MP@20fps, 4 MP@25fps, 1080p@25fps
Menu	
AGC	Support
D/N Mode	Auto/Color/BW (Black and White)
White Balance	ATW/MWB
BLC	Support
DWDR (Digital Wide Dynamic Range)	Support
Functions	Brightness, Sharpness, DNR, Mirror, Smart IR
Interface	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC
Power Consumption	E50TURBOZ: 6.3 W
Protection Level	IP67
Material	Front cover: Metal Main body: Plastic
IR Range	Up to 40 m
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	84.5 x 92 wx 255.1 mm (3.33" x 3.62" x 10")
Weight	E50TURBOZ Approx. 665 g