

# Dimmable CFL & LED bulbs

**Compatible with Caséta® Wireless100W & 150W C·L® dimmers**



# Dimmable CFL & LED bulbs

## Compatible with C·L<sup>®</sup> dimmers

List updated March 18, 2016

This list is designed to help you select bulbs that are compatible with Lutron C·L dimmers. The CFL and LED bulbs on this list were extensively tested by Lutron; the Lutron C·L dimmers were evaluated by UL and meet applicable safety standards.

## How to use this list

If you already have a bulb:

Use the “Find” tool in your browser or PDF viewer to search for the model number that’s printed on the bulb. Then choose a C·L dimmer that’s compatible with that bulb.

If you already have a C·L dimmer:

Use the table of contents to find the corresponding pages for that control, and then select a bulb from that list.

## What does “compatible” mean?

Compatible means that the bulbs can be dimmed, although the bulb’s dimming performance may not match what you’re used to seeing when dimming an incandescent or halogen bulb. These bulbs have also been electrically tested to confirm that the control may be used up to its full rated CFL/LED load without affecting the life of the control.

Products on this list are considered compatible with the respective Lutron C·L dimmers. Depending on the quality of the bulb you select, compatible bulbs may still:

- have less dimming range than an incandescent or halogen bulb
- dim less smoothly than an incandescent or halogen bulb
- flicker or shimmer at certain light levels
- buzz

# Dimmable CFL & LED bulbs

## Compatible with C•L® dimmers

List updated March 18, 2016

### For more information

If you'd like more information regarding bulb performance and test results, including dimming range, other dimmer options, and performance, please visit [www.lutron.com/ledtool](http://www.lutron.com/ledtool).

Warranty on your Lutron 100W C•L dimmer or 150W C•L dimmer will be void if used with bulbs that are not on this Lutron compatible bulb list.

Please note: Bulb variations in lamp design and construction affect performance. Bulb manufacturers can modify their bulbs at any time, without notice to Lutron. This prevents Lutron from ensuring ongoing compatibility. For up-to-date specifications, performance, and/or any related recall information about the bulb, please visit the bulb manufacturer's website.

*This document provides information from manufacturers who are not Lutron agents or affiliates. The listing of a manufacturer or the existence of any external link to another website does not suggest that Lutron is endorsing the linked company, its products and/or its services. Purchasers should ask appropriate questions and request references before buying any products and/or entering a contract with any party. The information contained in this document is intended for illustrative and comparative purposes only, and is subject to change at any time. Lutron does not warrant that (a) the list of manufacturers is all-inclusive; (b) the information is complete, up-to-date, accurate and/or error-free; (c) the products and Lutron controls listed will always be compatible; and (d) that the information provided will be a viable or appropriate solution for your project needs. You are entirely responsible for and assume all risk for the use of the information.*

# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Caséta<sup>®</sup> Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Cree	6W	BA19-04527OMB-12DE26-3_1	A19 4Flow, 83CRI, 2700K, 460 Lumen, E26
	6W	BA19-04527OMF-12DE26-3U100	A19 4Flow, 2700K, 460 Lumen, E26
	6W	BA19-04550OMB-12DE26-3_1	A19 4Flow, 83CRI, 5000K, 460 Lumen, E26
	6W	BA19-04550OMF-12DE26-3U100	A19 4Flow, 5000K, 460 Lumen, E26
	9.5W	BA19-08027OMF-12DE26-2U100	A19, Soft White, 2700K, 800 Lumen, Medium base
	9.5W	BA19-08027OMF-12DE26-2U500	A19, 2700K, 800 Lumen, E26, 60WE, 4pk
	9.5W	BBR40-07627FLF-12DE26-1U_00	BR40, 2700K, 760 Lumen, Flood
	9.5W	BBR40-07650FLF-12DE26-1U10	BR40, 5000K, 760 Lumen, Flood
	10W	BA19-08027OMB-12DE26-3_1	A19, 4Flow, 2700K, 815 Lumen, E26, 83 CRI
	10W	BA19-08050OMB-12DE26-3_1	A19, 4Flow, 5000K, 815 Lumen, E26, 83 CRI
	10.5W	BPAR30L-0853025C-12DE26-1C100	PAR30L, 3000K, 850 Lumen, 25° Spot
	10.5W	BPAR30L-0853040C-12DE26-1C100	PAR30L, 3000K, 850 Lumen, 40° Flood
	10.5W	BPAR30S-0853040C-12DE26-1C100	PAR30S, 3000K, 850 Lumen, 40° Flood
	11.5W	DRDL4-05727009-12DE26-1C100	4" Downlight, 2700K TW, 575 Lumen, E26 retrofit
	12.5W	DRDL6-06227009-12DE26-1C100	6" Downlight, 2700K TW, 625 Lumen, E26 retrofit
	12.5W	DRDL6-06250009-12DE26-1C100	6" Downlight, 5000K TW, 625 Lumen, E26 retrofit
	15W	DRDL6-11027009-12DE26-1C100	6" Downlight, 2700K, 1100 Lumen
	16.5W	BPAR38-1503027T-12DE26-2U_00	PAR38, 3000K, 1510Lm, E26, Spot
	16.5W	BPAR38-1503047T-12DE26-2U_00	PAR38, 3000K, 1510Lm, E26, Flood
	18W	BA21-16027OMF-12DE26-1U100	A21, 2700K, 1600 Lumen, E26, 18W
	18W	BA21-16050OMF-12DE26-1U100	A21, 5000K, 1600 Lumen, E26, 18W
	18W	BPAR38-1503027T-12DE26-1U100	PAR38, 3000K, 1500 Lumen, 27 deg spot
	18W	BPAR38-1503047T-12DE26-1U100	PAR38, 3000K, 1500 Lumen, 47 deg flood
	5W	5020001XXYY	Candle, 2700K, 350 Lumens
	5.5W	5bHPR500STW1D18	PAR20, 3000K 450Lm, E26
	5.5W	5bHPR500STW1D19	PAR20, 5000K 470Lm, E26
	6.5W	50217013006	PAR20, 3000K, 450 Lumens
	7W	ECS BR20 50WE CW 120 G1 BL	BR20, Daylight, 5000K, 525 Lumen, E26
	8W	ECS 20 CW FL 50WE 120	PAR20, 5000K, 490 Lumen
	8W	ECS 20 WW FL 50WE 120	PAR20, 3000K, 450 Lumen
	9W	5bSA800STQ1D02	A19, 3000K, 800Lm, E26, 4pk
	9W	A810SS-Q1D-01 (5bSA800STQ1D01)	A19, 2700K, 800Lm, E26
9W	A810SS-Q1D-04 (5bSA800STQ1D03)	A19, 5000K, 840Lm, E26, 4pk	
9.5W	5bHPR650STW1D29	PAR30, 3000K, 650Lm, E26	
9.5W	5bHPR650STW1D30	PAR30, 3000K, 680Lm, E26	
9.5W	ECS DN4 CW E26 120	4" Downlight, Daylight, 5000K, 650 Lumen, E26, retrofit	
9.5W	ECS DN4 CW GU24 120	4" Downlight, Daylight, 5000K, 650 Lumen, GU24 base, retrofit	
9.5W	ECS DN4 W27 E26 120	4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit	
9.5W	ECS DN4 W27 GU24 120	4" Downlight, Soft White, 2700K, 650 Lumen, GU24 base, retrofit	
9.5W	ECS DN6 CW GU24 120	6" Downlight, Daylight, 5000K, 650 Lumen, GU24 base, retrofit	
9.5W	ECS DN6 W27 GU24 120	6" Downlight, Soft White, 2700K, 650 Lumen, GU24 base, retrofit	
10W	DL-N14A10FR1-27	5/6" Downlight, 2700K, 650Lm, E26	
10W	DL-N14A10FR1-50	5/6" Downlight, 5000K, 650Lm, E26	
10W	DL-N14A10FR2-27	5/6" Downlight, 2700K, 650Lm, GU24	
10W	DL-N14A10FR2-50	5/6" Downlight, 5000K, 650Lm, GU24	
10W	ECS BR30 65WE CW 120 DG	BR30, Daylight, 5000K, 700 Lumen, E26	
10W	ECS BR30 65WE CW 120 DG 3PK	BR30, Daylight, 5000K, 700 Lumen, E26, 3pk	
10W	ECS BR30 65WE W27 120 DG	BR30, Soft White, 2700K, 650 Lumen, E26	
10W	ECS BR30 65WE W27 120 DG 3BX	BR30, Soft White, 2700K, 650 Lumen, E26, 3pk	
10W	ECS BR30 65WE WW 120 DG	BR30, Warm White, 3000K, 650 Lumen, E26	
10.5W	ECS 30 75WE WW GB FL 120	PAR30 Gimbal, 3000K, 750 Lumen, E26, 75WE	
10.5W	ECS 30 75WE xxx GB xx 120	PAR30 Gimbal, Various color temperatures, 75WE	

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K



# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Caséta<sup>®</sup> Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description	
EcoSmart	11W	5020901XYY†	BR30, 2700K, 770 Lumens	
	11.5W	ECS BR30 65WE CW 120	BR30, 5000K, Medium Base	
	11.5W	ECS BR30 65WE W27 120	BR30, 2700K, 650 Lumen, Medium Base	
	13W	5bHPR1000SW1D19	PAR38, 3000K, 900Lm, E26	
	13W	5bHPR1000SW1D20	PAR38, 5000K, 1000Lm, E26	
	14W	ECS BR40 90WE CW 120 DG	BR40, Daylight, 5000K, 1050 Lumen, E26	
Energetic	14W	ECS BR40 90WE W27 120 DG	BR40, 2700K, 1000 Lumen, E26	
	17.5W	ELY17D-2BRW-VB†	BR40, 2700K, 1100 Lumen	
	4.5W	R14DM/LED	R14, Soft White, 2700K, 300 Lumen, E26, 40WE	
	4.9W	BPCEFC/927/LED/3	Candle, 2700K, 330 Lumen, E12	
	6.5W	BPMPR16/GU10/DM/LED†	MR16, GU10 base	
	6.5W	MR16/GU10/DM/LED†	MR16, GU10 base	
	6.5W	R16DM/LED†	R16, Soft White, 2700K, 400 Lumen, E26, 40WE	
	8W	BPCEG25/927/LED/3	G25, 2700K, 495 Lumen, E26	
	8W	BPCER20/DM/LED	R20, 2700K, 450 Lumen, E26 Medium base (70 mA smooth reflector version)	
	8W	R20/927/LED	R20, 2700K	
	8W	R20/930/LED	R20, 3000K	
	8W	R20/950/LED	R20, 5000K,	
	8W	R20DM/LEDG2/CAN	R20, 2700K	
	8.5W	BR30M65/LED/6	R30, 650 Lumen, E26	
	Feit	9.7W	CELEDRT4/927	4" Downlight, 2700K, 520 Lumen, E26
		9.7W	EDRT4/927	4" Downlight, 2700K, 520 Lumen, E26
9.7W		LEDR4/827	4" Downlight, 2700K, 520 Lumen, E26	
9.7W		LEDR4/830	4" Downlight, 3000K, 520 Lumen, E26	
9.7W		LEDR4/850	4" Downlight, 5000K, 520 Lumen, E26	
9.7W		LEDRT4/927	4" Downlight, 2700K, 520 Lumen, E26	
9.7W		LEDRT4/940	4" Downlight, 4000K, 520 Lumen, E26	
13W		BPCEBR30LED	BR30	
13.5W		A19/OM800/5K/LED	A19, 5000K, Omni Directional	
13.5W		A19/OM800/LED	A19, 3000K, Omni Directional	
13.5W		BPCEA19/OM800/LED	A19, Omni Directional	
13.5W		BPCEA19/OM800/LED/CAN	A19, Omni Directional	
14W		LEDR56/830	Downlight, 3000K, 925 Lumen, retrofit kit	
17W		BR40/DM/LED†	BR40, 2700K, 1065 Lumen	
21.5W		CELEDRT56/927/2	5/6" Downlight, 2700K, 1250 Lumen, E26	
21.5W		LEDR56/827	5/6" Downlight, 2700K, 1250 Lumen, E26	
21.5W		LEDR56/927/MP/4	5/6" Downlight, 2700K, 1250 Lumen, E26, 4 pack	
21.5W		LEDR56HO/830	5/6" Downlight, 3000K, 1250 Lumen, E26	
21.5W		LEDR56HO/850	5/6" Downlight, 5000K, 1250 Lumen, E26	
GE	8W	LED8DA19/827	A19, 2700K, 450 Lumen, E26	
	10.5W	FAM45LED11DAV3H	A19, 2700K, 800 Lumens, E26, 2pk	
	14W	LED14DA21V2/827W	A21, 2700K, 1100 Lumen, E26	
Halo	12.2W	SLD405830WHR	4" Downlight, 3000K, 650 Lumen, E26 kit	
	12.2W	SLD405xxxxx	4" Downlight, 710-800 Lumen, 12W to 12.2W	
	12.2W	SLD606830WHR	5"/6" Downlight, 3000K, 675 Lumen, E26 kit	
	12.2W	SLD606xxxxx	5"/6" Downlight, 780-800 Lumen, 12.2W to 13.2W	
	13.2W	SLD606927WH	6" Downlight, 2700K, 780 Lumen	
	13.2W	SLD606927WHJB	6" Downlight, 2700K, 780 Lumen	
	13.2W	SLD606927WHR	6" Downlight, 2700K, 780 Lumen	
	13.2W	SLD606930WH	6" Downlight, 3000K, 780 Lumen	
	13.2W	SLD606930WHJB	6" Downlight, 3000K, 780 Lumen	
	13.2W	SLD606930WHR	6" Downlight, 3000K, 780 Lumen	
	13.2W	SLD606935WH	6" Downlight, 3500K, 780 Lumen	
	13.2W	SLD606935WHJB	6" Downlight, 3500K, 780 Lumen	
	13.2W	SLD606940WH	6" Downlight, 4000K, 780 Lumen	
	13.2W	SLD606940WHJB	6" Downlight, 4000K, 780 Lumen	

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K



## LED bulbs for Caséta<sup>®</sup> Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Halo	14.8W	SLD612827WHUNVJB	6" Downlight, 2700K, 1100 Lumen, E26
	14.8W	SLD612830WHUNVJB	6" Downlight, 3000K, 1150 Lumen, E26
	14.8W	SLD612835WHUNVJB	6" Downlight, 3500K, 1200 Lumen, E26
	14.8W	SLD612840WHUNVJB	6" Downlight, 4000K, 1215 Lumen, E26
	14.8W	SLD612927WHUNVJB	6" Downlight, 2700K, 880 Lumen, E26
	14.8W	SLD612930WHUNVJB	6" Downlight, 3000K, 925 Lumen, E26
	14.8W	SLD612935WHUNVJB	6" Downlight, 3500K, 965 Lumen, E26
	14.8W	SLD612940WHUNVJB	6" Downlight, 4000K, 1000 Lumen, E26
	Lighting Science	10.5W	LS 30 75WE xxx GB xx 120
11.5W		DFN BR30 65WE CW 120	BR30, Cool White, 5000K, Medium base
11.5W		DFN BR30 65WE NW 120	BR30, Neutral White, 4000K, Medium base
11.5W		DFN BR30 65WE W27 120	BR30, Warm White, 2700K, Medium base
11.5W		DFN BR30 65WE WW 120	BR30, Warm White, 3000K, Medium base
13W		LS GLP6 W27 120 WH S1 BX	6" Downlight, 2700K, E26 retrofit
Megaman	3.2W	LC1503.2DCS-E12-27K†	B10, 2700K, 250Lm, E12
Osram	13W	73396 (LEDRT56900827FL80)	5/6" Downlight, 2700K, 900 Lumen, E26
	3.5W	457226 (9290011668)†	Candle, 2700K, 180 Lumen, E12, Warm Glow
	3.5W	457234 (9290011668)†	Candle, 2700K, 180 Lumen, E12, Warm Glow
	3.5W	457242 (9290011668)†	Candle, 2700K, 180 Lumen, E12, Warm Glow
	4.5W	454371	PAR16, 3000K, 315 Lumens
	4.5W	9290002439	Candle, Warm White, 2700K, 320 Lumen, E26 base, Post Light
	4.5W	9290002797††	Candle, 2700K, 330 Lumen, E26, blunt tip
	4.5W	9290002889††	Candle, 2700K, 330 Lumen, E12, blunt tip
	4.5W	9290002890††	A15, 2700K, 330 Lumen, E12
	4.5W	9290002891††	A15, 2700K, 330 Lumen, E26
	4.5W	457119 (9290011673)	Candle, 330Lm, E26
	4.5W	457168 (9290011672)	G16.5, 330 Lm, E26
	4.5W	457184 (9290011670)	Candle, 330Lm, E12
	6W	9290002242	MR16, 3000K, 300 Lumen, GU10 base
	6W	456995 (9290011557)	R20, 2700K, 450 Lumen, Warm Glow
	6.5W	9290011347 (455741)	A19, Warm Glow, 450 Lumen
	7W	9290002706	A19 SlimStyle, Daylight, 5000K, 450 Lumen, E26
	8W	9290002267	A19, 2700K, 470 Lumen
	8W	9290002295	A19, 5000K, 470 Lumen
	8W	9290002329	PAR20, 3000K, 470 Lumen, E26
	8.5W	9290002543	BR30, 5000K, 730 Lumen, 8.5W
	9.5W	9290011117	BR30, 2700K, 730 Lumen, WarmGlow to 2200K (Nov 2014 or later)
	9.5W	9290011118 (452359)	BR30 SlimStyle, 2700K, 650 Lumen, E26, 65WE
	9.5W	9290011118 (452383)	BR30 SlimStyle, 2700K, 650 Lumen, E26, 65WE
	9.5W	9290011118 (452417)	BR30 SlimStyle, 2700K, 650 Lumen, E26, 65WE
	9.5W	9290011119 (452441)	BR30 SlimStyle, 5000K, 650 Lumen, E26, 65WE
	9.5W	9290011119 (452466)	BR30 SlimStyle, 5000K, 650 Lumen, E26, 65WE
	9.5W	9290011119 (452482)	BR30 SlimStyle, 5000K, 650 Lumen, E26, 65WE
	10W	458828 (9290011816)	A19, 2700K, 800 Lumen, 60WE, E26
	10W	459339 (9290011898)	G25, 2700K, 800 Lumen, E26
	10.5W	9290002544	BR30, 2700K, 730 Lumen
	10.5W	9290002707	A19 SlimStyle, Soft White, 2700K, 800 Lumen, 3pk
	11W	9290002268	A19, 2700K, 830 Lumen
	11W	9290002296	A19, 5000K, 830 Lumen
	11W	9290011113	PAR30L, 3000K, ? Lumen, E26
	12W	9290002580 (431392)	BR40, 2700K, 800 Lumen
	13W	9290011120	A21 SlimStyle, 2700K, 1100 Lumen
	13W	9290002523 13PAR38/F25 3000 DIM AF RO	PAR38, 3000K, 950 Lumen
	13W	9290011320 (454736)	PAR38, 2700K, 900 Lumen, E26
	13W	9290011321 (454744)	PAR38, 2700K, 900 Lumen, E26

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K





## LED bulbs for Caséta<sup>®</sup> Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description	
Philips	13W	9290011322 (454751)	PAR38, 2700K, 900 Lumen, E26	
	14W	459065	A19, 2700K, 1100Lm, 75WE, E26	
	14W	9290011839	A21, 2700K, 1100 Lumen, E26	
	15W	9290002595	A21, Soft White, 2700K, 1180 Lumen, E26	
	15W	9290011111	PAR38, 3000K, 1050 Lumen, E26, Flood	
	15W	9290011112	PAR38, 5000K, 1050 Lumen, E26, Flood	
	18W	9290011741	A21, 2700K, 1600Lumen, E26	
	18W	459107 (9290011741)	A21, 2700K, 1600 Lumen, E26	
	18W	459115 (9290011741)	A21, 2700K, 1600Lumen, E26	
	18W	459123 (9290011741)	A21, 2700K, 1600Lumen, E26	
	18W	459131 (9290011741)	A21, 2700K, 1600Lumen, E26	
	19W	453340	A19, 2700K, 1620Lm, 100WE, E26	
	19W	9290002577 (431395)	PAR38, 1300 Lumen, 25deg flood	
	19W	9290002578 (431403)	PAR38, 1300 Lumen, 35deg flood	
	Project Source	10W	DLS22-06B30D1E-WH-1	Downlight, 3000K, 650 Lumens, E26
Satco	8W	S9140	R20, 2700K, 525 Lumen, E26	
	8W	S9141	R20, 2700K, 525 Lumen, E26	
	8W	S9142	R20, 2700K, 525 Lumen, E26	
	8W	S9143	R20, 2700K, 525 Lumen, E26	
	11W	S9084	PAR30, 3000K, 780 Lumen, E26, short neck, 25° Beam	
	11W	S9085	PAR30, 4000K, 780 Lumen, E26, short neck, 25° Beam	
	11W	S9086	PAR30, 3000K, 780 Lumen, E26, short neck, 40° Beam	
	11W	S9087	PAR30, 4000K, 780 Lumen, E26, short neck, 40° Beam	
	11W	S9088	PAR30, 3000K, 780 Lumen, E26, long neck, 25° Beam	
	11W	S9089	PAR30, 4000K, 780 Lumen, E26, long neck, 25° Beam	
	11W	S9090	PAR30, 3000K, 780 Lumen, E26, long neck, 40° Beam	
	11W	S9091	PAR30, 4000K, 780 Lumen, E26, long neck, 40° Beam	
	13W	S9410	PAR30S, 2700k, 950 Lumen, E26	
	13W	S9415	PAR30S, 2700k, 950 Lumen, E26	
	13W	S9439	PAR30S, 2700k, 950 Lumen, E26	
	17W	S9092	PAR38, 3000K, 1200 Lumen, E26, 25° beam	
	17W	S9093	PAR38, 4000K, 1200 Lumen, E26, 25° beam	
	17W	S9094	PAR38, 3000K, 1200 Lumen, E26, 40° beam	
	17W	S9095	PAR38, 4000K, 1200 Lumen, E26, 40° beam	
	18W	S9455	PAR38, 3000K, 1400 Lumen, E26, Flood	
	18W	S9456	PAR38, 4000K, 1400 Lumen, E26, Flood	
	Solais	7W	LRP20/25/27K	PAR20, 2700K, 475 Lumen, E26, 25° Beam
		7W	LRP20/25/30K	PAR20, 3000K, 500 Lumen, E26, 25° Beam
		7W	LRP20/40/27K	PAR20, 2700K, 475 Lumen, E26, 40° Beam
		7W	LRP20/40/30K	PAR20, 3000K, 500 Lumen, E26, 40° Beam
11W		LR20/25/27K/675/xx	PAR20, 2700K, 675 Lumen, E26, narrow flood	
11W		LR20/25/30K/750	PAR20, 3000K, 750 Lumen, E26, narrow flood	
11W		LR20/40/27K/675/xx	PAR20, 2700K, 675 Lumen, E26, wide flood	
11W		LR20/40/30K/750/xx	PAR20, 3000K, 750 Lumen, E26, wide flood	
16W		LR30/10/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 10° Beam	
16W		LR30/10/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 10° Beam	
16W		LR30/10/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 10° Beam	
16W		LR30/15/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 15° Beam	
16W		LR30/15/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 15° Beam	
16W		LR30/15/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 15° Beam	
16W		LR30/25/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 25° Beam	
16W		LR30/25/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 25° Beam	
16W		LR30/25/30K/1200/WH	PAR30, 3000K, 1200 Lumen, E26, short neck, 25° Beam	
16W		LR30/40/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 40° Beam	
16W		LR30/40/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 40° Beam	
16W		LR30/40/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 40° Beam	
16W		LRP38/25/27K	PAR38, 2700K, 1025 Lumen, E26, 25° Beam	
16W		LRP38/25/30K	PAR38, 3000K, 1100 Lumen, E26, 25° Beam	

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K



## LED bulbs for Caséta<sup>®</sup> Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Solais	16W	LRP38/40/27K	PAR38, 2700K, 1025 Lumen, E26, 40° Beam
	16W	LRP38/40/30K	PAR38, 3000K, 1100 Lumen, E26, 40° Beam
	20W	LR38/25/30K/1450/SL	PAR38, 3000K, 1450 Lumen, E26, 15° Beam
	28W	LR38/15/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26
	28W	LR38/15/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26
	28W	LR38/25/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26
	28W	LR38/25/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26
	28W	LR38/40/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26
	28W	LR38/40/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26
	Sylvania	6W	79643
6.5W		79162 (LED6.5A19/DIM/O/850/G5)	A19, 5000K, 450 Lumen, E26
6.5W		79163 (LED6.5A19/DIM/O/850/G5)	A19, 2700K, 450 Lumen, E26
7W		75169	G25, 475 Lumen, E26
7W		75170	G25, 475 Lumen, E26
7W		75180	G25, 475 Lumen, E26
7W		79653 (LED7R20DIMSE830G3RP [LW])	R20, 3000K, 525 Lumen, E26,
7W		79659 (LED7R20/DIM/SE/830/G3)	R20, 3000K, 525 Lumen, E26,
7W		LED7A19/DIM/O/SE/830 (78214)	A19, 3000K to 2000K, 450 Lumen, E26, Sunset Effect
7W		LED7A19/DIM/O/SE/830/RP (78213)	A19, 3000K to 2000K, 450 Lumen, E26, Sunset Effect
8W		LED8A19DIMO827RP	A19, 2700K, 470 Lumen, E26
8W		LED8PAR16/DIM/930/FL36/P/LW	PAR16, Soft White, 390 Lumen
8W		LED8PAR16/GU10/DIM/930/FL36/RP	PAR16, GU10, Soft White, 390 Lumen
9W		79246 (LED9A19DIMO827G5)	A19, 2700K, 800 Lumen, E26
9W		79247 (LED9A9DIMO827G5)	A19, 2700K, 800 Lumen, E26
9W		79249 (LED9A19DIMO850RP)	A19, 5000K, 800 Lumen, E26
9W		79273 (LED9A19DIMO850G5RP)	A19, 5000K, 800 Lumen, E26
9W		79497 (LED9A19DIMO827G5CC)	A19, 2700K, 800 Lumen, E26
9W		LED9BR30/DIM/HO/850/G4	BR30, 800 Lumen, E26
9W		LED9BR30/DIM/HO/850/G4/RP	BR30, 800 Lumen, E26
9W		LED9BR30/DIM/HO/850/G4/RP2	BR30, 800 Lumen, E26
9W		LED9BR30/DIM/HO/G4/RP	BR30, 800 Lumen, E26
10W		LED10A19/DIM/O/SE/830	A19, 3000K, 800 Lumen
10W		LED10A19/DIM/O/SE/830/RP (78215)	A19, 3000K, 800 Lumen
10.5W		LED10A19/DIM/CL/O/827 (79146)	A19, 2700K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/827/BL (79147)	A19, 2700K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/827/G4 (79142)	A19, 2700K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/827/G4/BL (79143)	A19, 2700K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/827/RP (79644)	A19, 2700K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/850/G4 (79144)	A19, 5000K, 800 Lumen, E26, 60WE
10.5W	LED10A19/DIM/CL/O/850/G4/BL (79145)	A19, 5000K, 800 Lumen, E26, 60WE	
11W	79654 (LED11BR30DIMSE830G3RP[LW])	BR30, 3000K, 800 Lumen, E26	
11W	79657 (LED11BR30/DIM/SE/830/G3)	BR30, 3000K, 800 Lumen, E26	
11W	79660 (LED11BR30DIMSE830G3RP)	BR30, 3000K, 800 Lumen, E26	
11W	LED11BR30/DIM/HO/827/G3 (78413)	BR30, 2700K, 800 Lumen, E26	

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K



# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Caséta<sup>®</sup> Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description	
Sylvania	11W	LED11BR30/DIM/HO/827/G3/RP (78415)	BR30, 2700K, 800 Lumen, E26	
	11W	LED11BR30/DIM/HO/827/G3/RP (79121)	BR30, 2700K, 800 Lumen, E26	
	11W	LED11PAR20/DIM/930/FL30/P2	PAR20, Soft White, 550 Lumen	
	12W	LED12BR30/DIM/HO/827	BR30, 2700K, Medium base	
	12W	LED12BR30/DIM/HO/827/HVP	BR30, 2700K, Medium base	
	13W	73397-1	5/6" Downlight, 3000K, 900 Lumen, E26	
	13W	73422-1	5/6" Downlight, 3000K, 900 Lumen, E26	
	13W	73675-0	4/5/6" Downlight, 3000K, 900 Lumens, E26	
	13W	73676-0	4/5/6" Downlight, 3000K, 900 Lumens, E26	
	13W	LELD900830FL120	4/5/6" Downlight, 3000K, 900 Lumens, E26	
	14W	74031 (LED14PAR38DIM850FL40GL1WRP)	PAR38, 5000K, 1050 Lumen, E26	
	14W	74032 (LED14PAR38DIM830NFL25GL1W)	PAR38, 3000K, 1050 Lumen, E26	
	14W	74034 (LED14PAR38DIM830FL40GL1W)	PAR38, 3000K, 1050 Lumen, E26	
	14W	74035 (LED14PAR38DIM830NFL25GL1W)	PAR38, 3000K, 1050 Lumen, E26	
	14W	74036 (LED14PAR38DIM830WSP15GL1W)	PAR38, 3000K, 1050 Lumen, E26	
	14W	74037 (LED14PAR38DIM827FL40GL1W)	PAR38, 2700K, 1050 Lumen, E26	
	14W	74065 (LED14PAR38DIM850FL40GL1WRP)	PAR38, 5000K, 1050 Lumen, E26	
	14W	74066 (LED14PAR38DIM830FL40GL1WRP)	PAR38, 3000K, 1050 Lumen, E26	
	14W	74067 (LED14PAR38DIM830FL40GL1WRP)	PAR38, 3000K, 1050 Lumen, E26	
	15W	79655 (LED15BR40DIMSE830G3RP [LW]) <sup>†</sup>	BR40, 3000K, 1100 Lumen, E26	
	15W	79661 (LED15BR40DIMSE830G3RP) <sup>†</sup>	BR40, 3000K, 1100 Lumen, E26	
	15W	LED15BR40/DIM/SE/830/G3 <sup>†</sup>	BR40, 3000K, 1100 Lumen, E26,	
	17W	LED17PAR30LN/DIM/830/WSP15/P	PAR30, 3000K, 1200 Lumen, E26, spot	
	17W	LED17PAR30LN/DIM/830/WSP20	PAR30, 3000K, 1200 Lumen, E26, wide spot	
	20W	LED20PAR38/DIM/930/FL40/P2	PAR38, 3000K, 1000 Lumen,	
	21W	LED21/PAR38/DIM/P/930/FL30/HVP	PAR38, Warm White, 3000K, 1100 Lumen, E26, 21W	
	TCP	12W	LED12P30D27KNFL	PAR30, 2700K, 800 Lumen, E26
		17W	LED17BR40D27K (LED17BR40D)	BR40, 2700K, 1200 Lumen, E26
17W		LED17HOP38D27KNFL (LED17P38D1)	PAR38, 2700K, 1550 Lumen, E26, Narrow Flood	
17W		LED17P38D24KNFL	PAR38, 2400K, 1105 Lumen, E26	
Utilitech	3W	LG161/2DM/IF/LED <sup>†</sup>	G16.5, Warm White, 3000K, 200 Lumen, E12 base, frosted	
	4.5W	LR14DMLED	R14, Soft White, 2700K, 300 Lumen, E26, 40WE	

<sup>†</sup> Requires a minimum of 2 lamps

<sup>††</sup> Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K



# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Caséta<sup>®</sup> Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
	4.8W	LA15DM/CL/300/LED <sup>†</sup>	A15, Warm White, 3000K, 300 Lumen, E26, clear
	4.8W	LA15DM/IF/300/LED <sup>†</sup>	A15, Warm White, 3000K, 300 Lumen, E26, frosted
	4.8W	LA15DMC/CL/300/LED <sup>†</sup>	A15, Warm White, 3000K, 300 Lumen, E12 base, clear
	4.8W	LCFFDM/300/LED <sup>†</sup>	Candle, Warm White, 3000K, 300 Lumen, E12 base, frosted flame tip
	4.8W	LEFCDM/300/LED <sup>†</sup>	Candle, Warm White, 3000K, 300 Lumen, E26 base, clear flame tip
	4.8W	LG161/2DM/CL/300/LED <sup>†</sup>	G16.5, Warm White, 3000K, 300 Lumen, E12 base, clear
	4.8W	LG161/2DM/IF/300/LED <sup>†</sup>	G16.5, Warm White, 3000K, 300 Lumen, E12 base, frosted
	4.8W	LGMDM/CL/300/LED <sup>†</sup>	G16.5, Warm White, 3000K, 300 Lumen, E26, clear
	5.5W	LMR16GU10DMLEDG2	MR16, 2700K, 350 Lumen, GU10, Flood
	6.5W	LMR16/GU10/DM/LED <sup>†</sup>	MR16, GU10 base
	6.5W	LMR16DMGU10 <sup>†</sup>	MR16, GU10 base
	6.5W	LR16DMLED <sup>†</sup>	R16, Soft White, 2700K, 400 Lumen, E26, 40WE
	7.5W	R20/DM/5K/LED	R20, 450 Lumen, E26
	8W	BPCER20/927/LED	R20, 450 Lumen, E26
	8W	LCFCDM500LED <sup>†</sup>	Candle, 3000K, 500 Lumen, E12 candle base
	8W	LG25DM/LEDG2 <sup>†</sup>	G25, Warm White, 3000K, 510 Lumen, E26
	8W	LR20DMLEDG2	R20, 2700K, 450 Lumen, E26 Medium base (70 mA smooth reflector version)
	8W	R20/927/LED	R20, 450 Lumen, E26
	8W	R20/DM/LEDG2	R20, 450 Lumen, E26
	8W	R20DM/LEDG2/CAN	R20, 450 Lumen, E26
	8.5W	LMR16DMGU10/500/LED <sup>†</sup>	MR16, Warm White, 3000K, 520 Lumen, GU10, 120V
	8.5W	LPAR20LEDG72	PAR20, 500 Lumen, 2PK
	9W	LR20HO/LED/G2	R20, Soft White, 650 Lumen, E26, flood
	9W	R20HO/LED/G2	R20, Soft White, 650 Lumen, E26, flood
	9.5W	AGOM800/5K/LED/CAN	A19, 810 Lumen, E26
	9.5W	AGOM800/927/LED	A19, 810 Lumen, E26
	9.5W	AGOM800/927/LED/CAN	A19, 810 Lumen, E26
	9.5W	AGOM800/LED/3/CAN	A19, 800 Lumen, E26
	9.5W	AGOM800/LED/CAN	A19, 800 Lumen, E26
	9.5W	BPAGOM800/5K/LED	A19, 810 Lumen, E26
	9.5W	BPAGOM800/LED	A19, 800 Lumen, E26
	9.5W	BPAGOM800/LED/TAR	A19, 800 Lumen, E26
	9.5W	BPAGOM800/LED/TV	A19, 800 Lumen, E26
	9.5W	BPCEAG800/927/LED/3	A19, 810 Lumen, E26
	11W	DLS02-04A27D1E-WH-F1	4" Downlight, 2700K, 600 Lumen, E26 retrofit
	11W	DLS02-04A27D1E-WH-F2	4" Downlight, 2700K, 600 Lumen, E26 retrofit 2pk
	11W	DLS02-41127D1E-WF1	4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit
	11.5W	MQTL1017-LED11.5K850 <sup>†</sup>	Downlight, 5000K, 800 Lumen, E26 retrofit kit
	12W	LPAR30L/LEDG7/2	PAR30L, 3000K, 800 Lumen, E26, long neck, 2PK
	13W	BPCEBR30/927/LED	BR30, 750 Lumen, E26
	13W	BR30/927/LED	BR30, 750 Lumen, E26
	13W	BR30/927/LED/CAN	BR30, 750 Lumen, E26
	13W	BR30/DM/LEDG2	BR30, 750 Lumen, E26
	13W	BR30DM/LED/CAN	BR30, 750 Lumen, E26
	13W	DLS02-61327D1E-WF1	5" or 6" Downlight, Soft White, 2700K, 800 Lumen, E26 retrofit
	13W	DLS02-61350D1E-WF1	5" or 6" Downlight, Daylight, 5000K, 800 Lumen, E26 retrofit
	13W	DLS03-06E30D1E-WH-F1	Downlight 3000K 700 Lumens 65WE
	13W	LBR30DM/LEDG2	BR30
	13.5W	LA19/OM800/LED	A19, 3000K, 800 Lumen, Omni Directional
	15W	15PAR30L/LEDG5	PAR30, 3000K, 790 Lumen, E26
	15W	BPCEPAR30/930/LED	PAR30, 3000K, 770 Lumen, E26
	15W	LBR30HO/LED/G2	BR30, Soft White, 1150 Lumen
	15W	PAR30/S/5K/LEDG5	PAR30, 3000K, 750 Lumen, E26
	15W	PAR30/S/LEDG5	PAR30, 3000K, 750 Lumen, E26
	15W	PAR30L/5K/LEDG5	PAR30, 3000K, 800 Lumen, E26

Utilitech

† Requires a minimum of 2 lamps  
 †† Requires a minimum of 3 lamps  
 © Lutron Electronics Co., Inc. | PN 368-3266K

# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Caséta<sup>®</sup> Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Utilitech	15W	PAR30L/930/LED	PAR30, 3000K, 770 Lumen, E26
	15W	PAR30L/LEDG5	PAR30, 3000K, 800 Lumen, E26
	15.5W	BPCEAG1600/827/LED	A19, 1600 Lumen, E26
	16W	AGOM1600/5K/LED/CAN	A19, 1600 Lumen, E26
	16W	AGOM1600/LED/CAN	A19, 1600 Lumen, E26
	16W	BPAGOM1600/5K/LED	A19, 1600 Lumen, E26
	16W	BPAGOM1600/LED	A19, 1600 Lumen, E26
	16W	BPAGOM1600/LED/TAR	A19, 1600 Lumen, E26
	16W	LBR40DM/LEDG2	BR40, 1065 Lumen, E26
	16W	LPAR38LEDG72	PAR38, 3000K, 950 Lumen, 2PK
	16W	LPAR38LEDG72	PAR38, 3000K, 950 Lumen, 2PK
	16.5W	PAR38/5K/LEDG5	PAR30, 3000K, 1000 Lumen, E26
	17W	BPCEBR40/DM/LED <sup>†</sup>	BR40
	17W	LBR40DM/LED <sup>†</sup>	BR40, 2700K, 1065 Lumen
	17.5W	YGA08A35-17.5W-827 <sup>†</sup>	BR40, 2700K, 1100 Lumen
	18W	BPCEPAR38/930/LED	PAR30, 3000K, 950 Lumen, E26
	18W	PAR38/930/LED	PAR30, 3000K, 950 Lumen, E26
	20W	20PAR38/LEDG5	PAR30, 3000K, 1035 Lumen, E26
	20W	DLS24-06C27D1E-WH-F1	5 or 6" Downlight 2700K 1200 Lumens 90WE
	20W	LBR40HO/LED/G2	BR40, Soft White, 1400 Lumen
20W	PAR38/LEDG5	PAR30, 3000K, 950 Lumen, E26	
20.5W	LPAR381400LEDG72	PAR38, 1450 Lumen, 2PK	
Westinghouse	17W	33014	PAR38, 3000K, 1200 Lumen, flood
	17W	33064	PAR38, 3000K, 1200 Lumen, flood

† Requires a minimum of 2 lamps  
 †† Requires a minimum of 3 lamps  
 © Lutron Electronics Co., Inc. | PN 368-3266K

# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## CFL bulbs for Caséta<sup>®</sup> Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
GE	26W	FLE26HT3/2/DV/SW	Spiral
	14W	4R2014TD	R20, TruDim, 2700K
TCP	14W	4R2014TD30K	R20, TruDim, 3000K
	14W	4R2014TD35K	R20, TruDim, 3500K
	14W	4R2014TD41K	R20, TruDim, 4100K
	14W	4R2014TD50K	R20, TruDim, 5000K
	14W	4R2014TD65K	R20, TruDim, 6500K

† Requires a minimum of 2 lamps  
 †† Requires a minimum of 3 lamps  
 © Lutron Electronics Co., Inc. | PN 368-3266K

# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Caséta<sup>®</sup> Wireless plug-in lamp dimmer

Caséta Wireless plug-in lamp dimmer: PD-3PCL

Maximum wattage controlled: 100W



Brand	Wattage	Model	Description	
Cree	6W	BA19-04527OMF-12DE26-1U100	A19, Warm Soft White, 2700K, 450 Lumen, Medium base	
	6W	BA19-04527OMF-12DE26-2U100	A19, Warm Soft White, 2700K, 450 Lumen, Medium base	
	6W	BA19-04550OMF-12DE26-2U500	A19, 5000K, 450 Lumen, 40WE, 4pk	
	9.5W	BA19-08027OMF-12DE26-2U100	A19, Soft White, 2700K, 800 Lumen, Medium base	
	9.5W	BA19-08027OMF-12DE26-2U500	A19, 2700K, 800 Lumen, E26, 60WE, 4pk	
	18W	BA21-16027OMF-12DE26-1U100	A21, 2700K, 1600 Lumen, E26, 18W	
Feit	18W	BA21-16050OMF-12DE26-1U100	A21, 5000K, 1600 Lumen, E26, 18W	
	9.5W	BPCER20/DM/LED	PAR20	
	9.5W	PAR20/5K/LEDG5	PAR20, 5000K	
	9.5W	PAR20/5K/LEDG5/CAN	PAR20, 5000K	
	9.5W	PAR20/LEDG5	PAR20, 3000K, 450 Lumen	
	9.5W	PAR20/LEDG5/CAN	PAR20	
	13.5W	A19/OM800/5K/LED	A19, 5000K, Omni Directional	
	13.5W	A19/OM800/LED	A19, 3000K, Omni Directional	
	13.5W	BPCEA19/OM800/LED	A19, Omni Directional	
	13.5W	BPCEA19/OM800/LED/CAN	A19, Omni Directional	
GE	18W	LED18D38W827/15	PAR38, 2700K, E26, 15° Beam	
	18W	LED18D38W827/25	PAR38, 2700K, E26, 25° Beam	
	18W	LED18D38W827/40	PAR38, 2700K, E26, 40° Beam	
	18W	LED18D38W830/15	PAR38, 3000K, 1400 Lumen, E26, 15° Beam	
	18W	LED18D38W830/25	PAR38, 3000K, 1400 Lumen, E26, 25° Beam	
	18W	LED18D38W830/40	PAR38, 3000K, 1400 Lumen, E26, 40° Beam	
	18W	LED18D38W927/15	PAR38, 2700K, 1100 Lumen, E26, 15° Beam	
	18W	LED18D38W927/25	PAR38, 2700K, 1100 Lumen, E26, 25° Beam	
	18W	LED18D38W927/40	PAR38, 2700K, 1100 Lumen, E26, 40° Beam	
	18W	LED18D38W930/15	PAR38, 3000K, 1200 Lumen, E26, 15° Beam	
	18W	LED18D38W930/25	PAR38, 3000K, 1200 Lumen, E26, 25° Beam	
	18W	LED18D38W930/40	PAR38, 3000K, 1200 Lumen, E26, 40° Beam	
	Philips	8W	9290002267	A19, 2700K, 470 Lumen
		8W	9290002295	A19, 5000K, 470 Lumen
9.5W		455840 (9290011345)	A19, Soft White, 2200-2700K, 800 Lumen, E26	
11W		9290002268	A19, 2700K, 830 Lumen	
11W		9290002296	A19, 5000K, 830 Lumen	
13W		9290011120	A21 SlimStyle, 2700K, 1100 Lumen	
Satco	15W	9290002595	A21, Soft White, 2700K, 1180 Lumen, E26	
	10.5W	S9037	A19, 2700K, 810 Lumen, E26	
	10.5W	S9038	A19, 3500K, 830 Lumen, E26	
Sylvania	10.5W	S9039	A19, 5000K, 870 Lumen, E26	
	8W	LED8A19DIMO827RP	A19, 2700K, 470 Lumen, E26	
	10.5W	LED10A19/DIM/CL/O/827 (79146)	A19, 2700K, 800 Lumen, E26, 60WE	
	10.5W	LED10A19/DIM/CL/O/827/BL (79147)	A19, 2700K, 800 Lumen, E26, 60WE	
	10.5W	LED10A19/DIM/CL/O/827/G4 (79142)	A19, 2700K, 800 Lumen, E26, 60WE	
	10.5W	LED10A19/DIM/CL/O/827/G4/BL (79143)	A19, 2700K, 800 Lumen, E26, 60WE	
	10.5W	LED10A19/DIM/CL/O/827/RP (79644)	A19, 2700K, 800 Lumen, E26, 60WE	
	10.5W	LED10A19/DIM/CL/O/850/G4 (79144)	A19, 5000K, 800 Lumen, E26, 60WE	
	10.5W	LED10A19/DIM/CL/O/850/G4/BL (79145)	A19, 5000K, 800 Lumen, E26, 60WE	
	11W	73195-0	Downlight	
11W	73497-0	Downlight		
Utilitech	7.5W	LA19DM/LEDG2	A19, 3000K, 450 Lumen	
	8W	LG25DM/LEDG2	G25, Warm White, 3000K, 510 Lumen, E26	
	9.5W	LPAR20/5K/LEDG5	PAR20, 5000K, 500 Lumen	
	9.5W	LPAR20/LEDG5	PAR20, 3000K, 450 Lumen	

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K



# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Caséta<sup>®</sup> Wireless plug-in lamp dimmer

Caséta Wireless plug-in lamp dimmer: PD-3PCL

Maximum wattage controlled: 100W



Brand	Wattage	Model	Description
Utilitech	9.5W	LPAR20DM/SP/LED	PAR20, 3000K, 465 Lumen, Spot
	13.5W	LA19/OM800/LED	A19, 3000K, 800 Lumen, Omni Directional
	16W	LBR40DM/LEDG2	BR40, 1065 Lumen, E26

† Requires a minimum of 2 lamps  
 †† Requires a minimum of 3 lamps  
 © Lutron Electronics Co., Inc. | PN 368-3266K



# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## CFL bulbs for Caséta<sup>®</sup> Wireless plug-in lamp dimmer

Caséta Wireless plug-in Lamp dimmer: PD-3PCL

Maximum wattage controlled: 100W



Brand	Wattage	Model	Description
GE	26W	FLE26HT3/2/DV/SW	Spiral

† Requires a minimum of 2 lamps  
†† Requires a minimum of 3 lamps  
© Lutron Electronics Co., Inc. | PN 368-3266K