

DS-2CD2121G1-IDW

2 MP IR Fixed Dome Wi-Fi Network Camera



- High quality imaging with 2 MP resolution
- Efficient H.265+ compression technology
- Clear imaging even with strong back lighting due to DWDR technology
- Up to 128 GB SD card slot for storage
- Built-in microphone for real-time audio security
- Wi-Fi connection and easy installation
- Water and dust resistant (IP66)



▪ Specification



| Camera | |
|---------------------|---|
| Image Sensor | 1/2.8" Progressive Scan CMOS |
| Min. Illumination | Color: 0.028 Lux @(F2.0, AGC ON) |
| Shutter Speed | 1/3 s to 1/100,000 s |
| Slow Shutter | Yes |
| Day & Night | IR Cut Filter |
| Wide Dynamic Range | DWDR |
| DNR | 3D DNR |
| Axis Adjustment | Pan: 0° to 355°, tilt: 0° to 75° |
| Lens | |
| Auto-Iris | No |
| Aperture | F2.0 |
| Focus | No |
| FOV | 2.8 mm, horizontal FOV: 114°, vertical FOV: 62°, diagonal FOV: 135° 4 mm, horizontal field of view: 86°, vertical FOV: 46°, diagonal FOV: 102° |
| Lens Mount | M12 |
| Focal Length | 2.8/4 mm |
| Illuminator | |
| IR Range | Up to 30 m |
| Wavelength | 850 nm |
| Video | |
| Max. Resolution | 1920 × 1080 |
| Main Stream | 50Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30 fps (1920 × 1080, 1280 × 960, 1280 × 720) |
| Sub Stream | 50Hz: 25 fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30 fps (640 × 480, 640 × 360, 320 × 240) |
| Video Compression | Main stream: H.265/H.264 Sub-stream: H.265/H.264/MJPEG |
| H.264 Type | Baseline Profile/Main Profile/High Profile |
| H.265 Type | Main Profile |
| Video Bit Rate | 32 Kbps to 8 Mbps |
| Audio | |
| Audio Compression | G.711/G.722.1/G.726/MP2L2/PCM |
| Audio Bit Rate | 64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2) |
| Audio Sampling Rate | 8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz |
| Smart Feature-Set | |
| Region of Interest | Support 1 fixed region for main stream |
| Image | |
| Image Enhancement | BLC/3D DNR |
| Image Setting | Saturation, brightness, contrast and sharpness are adjustable via client software and web browser |
| Day/Night Switch | Auto/Scheduled/Day/Night |

| Wi-Fi | |
|----------------------------------|--|
| Wireless Standards | IEEE802.11b, 802.11g, 802.11n |
| Frequency | 2.412 GHz - 2.472 GHz |
| Channel Bandwidth | 20/40MHz |
| Security | 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS |
| Transfer Rate | 11b/g: 54 Mbps 11n: up to 150 Mbps |
| Wireless Range | Up to 50 m (The performance varies based on actual environment) |
| Network | |
| Alarm Trigger | Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD error, HDD full |
| Network Storage | Support built-in microSD/SDHC/SDXC card (128 GB), local storage and NAS (NFS, SMB/CIFS), ANR |
| Protocols | 802.11b: CCK, QPSK, BPSK 802.11g/n: OFDM |
| API | ONVIF (PROFILE S, PROFILE G), ISAPI |
| Simultaneous Live View | Up to 6 channels |
| User/Host | Up to 32 users. 3 levels: administrator, operator and user |
| Client | Wired network: Hik-Connect, iVMS-4200, iVMS-5200, iVMS-4500 Wi-Fi: iVMS-4200, iVMS-5200, iVMS-4500 |
| Web Browser | IE 8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+ |
| Interface | |
| Communication Interface | 1 RJ45 10M/100M self-adaptive Ethernet port |
| Audio | 1 Built-in mic, mono sound |
| Alarm | No |
| Video Output | No |
| On-board Storage | Built-in microSD/SDHC/SDXC slot, up to 128 GB |
| General | |
| Firmware Version | V5.5.98 |
| General Function | One-key reset, anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter |
| Reset | Yes |
| Startup and Operating Conditions | -30 °C to +60 °C (-22 °F to +140 °F), humidity 95% or less (non-condensing) |
| Power Supply | 12 VDC ± 25%, Ø5.5 mm coaxial plug power |
| Power Consumption and Current | 12 VDC, 0.4 A, max: 5 W, <20 dBm |
| Material | Plastic |
| Dimensions | Camera: Ø121.4 mm × 92.2 mm (Ø4.8" × 3.6") With package: 150 mm × 150 mm × 141 mm (5.9" × 5.9" × 5.6") |
| Weight | Camera: 465 g (1 lb.) With package: 713 g (1.6 lb.) |
| Approval | |
| Protection | Ingress protection: IP66 (IEC 60529-2013) |
| Compression Standard | |
| H.264+ | Main stream supports |

H.265+

Main stream supports

▪ Dimension



Unit: mm(inch)

▪ Available Model

DS-2CD2121G1-IDW1(2.8 mm, 4 mm)

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com