

Archer C80

CARACTERÍSTICAS DE HARDWARE

Interface 4 10/100/1000Mbps LAN Ports

1 10/100/1000Mbps WAN Port

Botón Reset Button

WPS/Wi-Fi Button

Power On/off Button

Fuente de Alimentación Externa US version 12V/1.5A

EU version 12V/1A

Dimensiones (W X D X H) 8.5 x 4.6 x 1.26 in (215 x 117 x 32 mm)

Antena 4 Fixed Omni Directional Antennas



CARACTERÍSTICAS INALÁMBRICAS

Estándares Inalámbricos IEEE 802.11a/n/ac 5 GHz

IEEE 802.11b/g/n 2.4 GHz

Frecuencia 2.4 GHz and 5 GHz

Tasa de Señal 1300 Mbps on 5 GHz + 600 Mbps on 2.4 GHz

Sensibilidad de Recepción 5 GHz:

11a 6Mbps:-98dBm, 11a 54Mbps:-78dBm

11ac VHT20_MCS0:-98dBm, 11ac VHT20_MCS8:-72dBm

11ac VHT40_MCS0:-92dBm, 11ac VHT40_MCS9:-68dBm

11ac VHT80_MCS0:-89dBm, 11ac VHT80_MCS9:-64dBm

2.4 GHz:

11g 6Mbps:-97dBm, 11a 54Mbps:-77dBm

11n VHT20_MCS0:-97dBm, 11n VHT20_MCS8:-72dBm

11n VHT40_MCS0:-92dBm, 11n VHT40_MCS9:-67dBm

Potencia de Transmision CE: <20dBm(2.4 GHz), <23dBm(5.15 GHz~5.25 GHz)

FCC:<30dBm(2.4 GHz & 5 GHz)

Funciones Inalámbricas Enable/Disable Wireless Radio, WMM

Seguridad Inalámbrica 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions

Red de Invitado 2.4 GHz Guest Network, 5 GHz Guest Network

CARACTERÍSTICAS DE SOFTWARE

Calidad de servicio Device Prioritization

WAN Type Dynamic IP/Static IP/PPPoE(Dual Access)/PPTP(Dual Access)/L2TP(Dual Access)

Administración Parental Controls, Local Management, Remote Management

DHCP Server, DHCP Client List, Address Reservation

Port Forwarding Port Forwarding, Port Triggering, UPnP, DMZ

Dynamic DNS DynDns, NO-IP, TP-Link

Control de Acceso Local Management Control, White List, Black List

Seguridad de cortafuegos SPI Firewall, IP and MAC Address Binding

Protocolos Supports IPv4 and IPv6

Características Avanzadas MU-MIMO

Beamforming

Smart Connect

Airtime Fairness

Quality of Service

OTROS

Certificacion CE, FCC, RoHS

Contenidos del Paquete Wireless Router Archer C80

Power Adapter

RJ45 Ethernet Cable

Quick Installation Guide

Requisitos del Sistema Microsoft Windows 98SE/NT/2000/XP/Vista™/7/8/8.1/10, MAC OS,

NetWare, UNIX or Linux

Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other

Java-enabled browser

Cable or DSL Modem

Subscription with an internet service provider (for internet access)

Ambiente Operating Temperature: 0°C~40°C (32°F ~104°F)

Storage Temperature: -40°C~70°C (-40°F ~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing