

HX424C15FB3 / HX426C16FB3 / HX432C16FB3

SPECIFICATIONS AND DIMENSIONS



Form Factor	UDIMM
Pins	288
XMP Ready	Yes
Plug N Play	Yes
Speeds	2400, 2666, 3000, 3200, 3466
CAS Latencies	15, 16
Voltage	1.2V, 1.35V
Module Capacities	4GB, 8GB, 16GB
Kit Capacities	8GB, 16GB, 32GB, 64GB
Kit Configurations	Dual Channel, Quad Channel
Operating Temperature	0° C to +85° C
Storage Temperature	-55° C to +100° C
PCB Color	Black
Heat Spreader Colors	Black
Module Dimensions	133.35mm x 34.1mm x 7.2mm
Warranty	Lifetime

UNLEASH YOUR STYLE. UNLEASH YOUR FURY.

HyperX® FURY DDR4 auto-overclocks itself to the highest published frequency, up to 3466MHz¹, providing a Plug N Play boost for gaming, video editing, and rendering. FURY DDR4 is XMP-ready and available in 2400MHz–3466MHz speeds, CL15–16 latencies, single module capacities of 4GB–16GB, and kit capacities of 16GB–64GB. It features Plug N Play automatic overclocking at 2400MHz and 2666MHz speeds and is compatible with the latest Intel and AMD CPUs. HyperX FURY DDR4 stays cool with its stylish, low-profile heat spreader. 100% tested at speed and backed by a lifetime warranty, FURY DDR4's your worry-free, cost-effective upgrade of choice.