

Tapo C100

Input Trigger Detección de Movimiento

Output Notification Envío de Notificaciones

VIDEO

Video Compression H.264

Video Streaming 1080p

SYSTEM

Regulatory Certification FCC, IC, CE, NCC

System Requirements iOS 9+, Android 4.4+

ENVIRONMENT

Operating Temperature 0-40 °C (32-104 °F)

Storage Temperature -40-70 °C (-40-158 °F)

Operating Humidity 10-90% RH Sin Condensación

Storage Humidity 5-90% RH Sin Condensación

PACKAGE CONTENTS

Package Contents Cámara Tapo C100

Adaptador de Corriente

Guía de Inicio Rápido

Tornillos de Montaje

Plantilla de montaje

HARDWARE

Button Botón Reset

Indicator LED Sistema LED

Adapter Input 100-240V, AC, 50/60 Hz, 0.3 A

Adapter Output 9.0 V / 0.6 A

Dimensions (W x D x H) 67.6 x 54.8 x 98.9 mm (2.7 x 2.1 x 3.9 in)

CÁMARA

Sensor de Imagen 1/3.2"



Motion Detection



Sound and Light Alarm



Night Vision



1080p Full HD
1080p Crystal Clear Image



Up to 128 GB
(card not included)



Privacy Mode

Resolución 1080p Full HD

Lentes F/NO: 2.0, Longitud Focal: 3.3 mm

Night Vision 850 nm IR LED (up to 30 ft)

AUDIO

Comunicación de Audio Audio Doble Sentido

Audio Input & Output: Micrófono y Altavoz

RED

Seguridad 128 Bit AES Encryption with SSL/TLS

Wireless Rate 11 Mbps (802.11 b)

54 Mbps (802.11 g)

150 Mbps (802.11 n)

Frequency 2.4 GHz

Wireless Security WEP, WPA, WPA2-PSK