




No PoE Detected



Mid-span 802.3af/at
PoE Injector / Injector Hub



End-span 802.3af/at
PoE Switch



4-pair 60-watt
PoE Injector

POETESTER

Specifications

Interface	<ul style="list-style-type: none"> 1 x RJ-45 TP connector PoE Power Input (PD)
LED indicators	<ul style="list-style-type: none"> End-span / Pin 1236 (Green) <ul style="list-style-type: none"> The PoE voltage is detected on pair 1,2,3,6 Mid-span / Pin 4578 (Orange) <ul style="list-style-type: none"> The PoE voltage is detected on pair 4,5,7,8
Power input	IEEE 802.3at/af compliant with voltage within 36~57V
Temperature	-10° to 60°C (operating)
Humidity	5% to 95% (non-condensing)
Dimensions (DxWxH)	70.1 x 23 x 22 mm
Weight	20g
Cabling	UTP: Cat. 5 UTP cable or above, 100m (maximum)
Standard	<ul style="list-style-type: none"> IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet Plus
Emission	CE Compliance



Power over Ethernet

▶ POE-TESTER

IEEE 802.3af/at Power over Ethernet Tester

- ▶ Easily tests RJ-45 outlet for Power over Ethernet existence in a second
- ▶ Two LEDs indicate the types of PSE (Power Source Equipment)
 - End-span PoE Switch
 - Mid-span PoE Injector / Injector Hub
 - 4-pair 60-watt Ultra PoE Injector
- ▶ Compliant with IEEE 802.3at/af standard
- ▶ Compact size, Plug and Play design



POETESTER



2010-AF0460-000

PLANET reserves the right to change specification without prior notice.
All brand names and trademarks are property of their respective owners.
Copyright © 2013 PLANET Technology Corp. All rights reserved.

PLANET Technology Corporation
▶ www.planet.com.tw



Made in Taiwan