

## AC Standard

	Items	Basic (Free)	AC Standard
Device	Max. Device	1,000	1,000
	Max. Slave per Master (RS-485)	31 (Up to 8 Fingerprint Devices)	31 (Up to 8 Fingerprint Devices)
	RS-485 Protocol	OSDP Supported	OSDP Supported
	Multi-Door Control	Supported	Supported
	Device Admin Level	All / User / Config	All / User / Config
	Auto Reconnection to Server	Direct & Server mode	Direct & Server mode
	USB Enrollment Device	BioMini, DUALi DE-620	BioMini, DUALi DE-620
User	Max. Card per User	8	8
	Max. Fingerprint per User	10	10
	Auto User Sync to Device	Supported	Supported
	Access-on-Card	Supported	Supported
	Secure Credential	Supported	Supported
	Inactive User Report	Supported	Supported
	Custom Fields	Supported	Supported
Access Control	Max. Access Level	128	128
	Max. Access Group	128	128
	Max. Access Group per User	16	16
	Max. Door per Access Level	128	128
	Auto Access Group Sync to Device	Supported	Supported
	Access Group Report by Door/User/Elevator	Supported	Supported
Elevator (Floor Management)	Max. Elevator	-	1,000
	Max. Floor per Elevator	-	192
	Max. Floor Level	-	128
	Dual Auth	-	Supported
	Anti-passback Zone	-	Supported
	Fire Alarm Zone	-	Supported
Zone	Max. Zones	-	100
	Max. Device per Zone	-	1,000 Global, 32 Local
	Anti-passback	Single Door APB	Global, Local
	Fire Alarm	-	Global, Local
	Scheduled Unlock/Lock	-	Supported
	Intrusion Alarm	-	Supported (Local)
Advanced	Dashboard	Supported	Supported
	Server Matching	-	Supported
	Audit Trail	Supported	Supported
	Video Log	-	Supported
	BioStar 2 Mobile App	Supported (User, Door, Monitoring, Alarm, Mobile Card)	Supported (User, Door, Monitoring, Alarm, Mobile Card)

## TA Standard

Items	Basic (Free)	TA Standard
Number of Shifts	Unlimited	Unlimited
Number of Schedules	1	Unlimited
Number of User per Schedule	99	Unlimited
Shift Type	Fixed, Flexible	Fixed, Flexible
Time Card	Supported	Supported
Number of Leave per User	Unlimited	Unlimited
Calendar View	Supported	Supported