

#### Descripción

Modelo: PRORG59VW

# RG 59+2C Coaxial +Power Cable

# **Specification:**

## Coaxial part:

Conductor material: Pure Copper (99.99% of copper)

Conductor size: 1/0.8±0.02mm Insulation: Foam PE(3.7±0.03mm)

First Shielding: AL Foil

Second Shielding: 64\*0.12mm CCA braiding

Jacket: PVC Color: White (6.0±0.15mm)\*(11.3±0.3mm)

PRORG59VW: 150 M/ Drum

## Power cable part:

Conductor material: copper clad aluminum(CCA)


Conductor size: 7/0.38±0.02mm

Conductor number:2

• Insulation color: Red, Black

Jacket: PP/PE





#### **Characteristics:**

Coaxial part Conductor:	
Number of conductor	1
Material	Solid Bare Conductor
Size	1/0.8±0.02mm
Coaxial part Insulation:	
Material	(3.7±0.03mm)
Avg.Thickness	1.6mm
Diameter	3.7±0.03mm
Coaxial part Shielding:	
First Shielding	Aluminum Foil tape
Second Shielding	64*0.12mm CCA braiding
Power cable part	
Number of conductor	2
Conductor Material	Copper Clad Aluminum(CCA)

Conductor Size	7/0.38±0.02mm	
Insulation Color	Red, Black	
Jacket		
Material	PVC	
Size	(6.0±0.15mm)*(11.3±0.3mm)	

#### **Features:**

- Fast and Reliable Connection
- Durable and Reasonable Design of the Structure Realizes the High Performance
- Wide Frequency Range
- Fine Shields Protect the Data Transmission and Reduce the Interference
- New Design of the Jacket Shows the Sense of Technology and Smartness
- Jacket Color in Lucidity, Lucidity Blue, Black, White or as per Your Requirement

## **Application:**

- Lan Network System
- Computer Network Distribution System
- Testing Equipment and CATV System
- Video field, communication system and control system; Video monitoring lines, radio signal control, public TV antennas, closed-circuit television monitoring system, radio communication, transmission system and control one-way or high frequency equipment of internal thread.

