

## Audio Wire 18 AWG Un-shielded

Model Number:PROAUDIO/500



### Application

Voice,Speakers, Microphones Applications  
Flexible Cable for Easy Installations  
Ideal for any Audio System  
Auto-control Systems

### Standards

ISO 9001:2000  
PVC Comply with the ROHS Directive 2002/95/EC

### Flame resistance

IEC 60332-1  
CM

### Physical Characteristics

Conductor	18 AWG 7-STR Annealed Bare Copper Conductors
Insulation	FRNC Polyvinyl chloride, Ø 1.55±0.02 mm
Insulation Avg. Thickness	0.011"   0.28mm
Insulation Color	Black & Red
Twisting	2 Insulation twisted to the pair, 12.5 twists per meter
Rip Cord	Yes
Shielded	N/A
Sheath	CM Rated Polyvinyl chloride,Ø 4.1±0.2 mm
Sheath Avg. Thickness	0.0196"   0.50mm
Sheath Color	White RAL 9003

### Electrical properties @ 20°C

DC resistance	Max 23.00 ohm/1000M at 20°C
Mutual capacitance	96.5 pf/M
Characteristic impedance 100 MHz	64 ± 5 Ω
Nominal velocity of propagation	approx. 55 %
Voltage Rating	300 V
Max. Current	3.75 A @ 20°C
Temperature	-20°C to 60 °C

### Product Code Table

Product Description	Packing Length	Part Number
18 AWG STR AUDIO CABLE Un-shielded White	500ft Color box	PROAUDIO/500

© SYSCOM, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Syscom: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Syscom. The information is believed to be correct at the time of issue. Syscom reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Syscom.