


NOTES:

1. REMOVE ALL BURRS AND SHARP EDGES.
2. STS-10.0 TUBES ARE CUT IN HALF AND PACKAGED WITH CONNECTOR (BRIDGESPOINT DC-240)
3. DISTANCE BTWN THE CENTERS OF THE HOLES SIZE 1.5"±1/32, 3"±1/16, 6"±1/16
4. TOTAL BTWN 1ST AND LAST HOLE SIZE 2.5'±1/16, 10'±1/8, AND 5'±1/16 FOR LESS THAN 19 HOLES ±1/8
5. HOLE DIA MAX 9/64 MIN 7/64.
6. HOLE DISLOCATION FROM THE CENTER LINE TO BE 1/16"

STS-10.0 P/N 0400-01570
 STS-2.5 P/N 0400-01580
 STS-5.0 P/N 0400-01590

REV.	DATE	BY	INITIAL RELEASE	CHANGE
-	02-13-02	BM	INITIAL RELEASE	

TOLERANCE UNLESS OTHERWISE SPECIFIED		DRAWN BY: BEN MAGARIN	
SIZE	TOL.	CHECKED BY:	UNES
10'	+1/2"		IN
5'	+1/4"	APPROVED BY:	SCALE
2.5'	+1/8"		NTS
MATERIAL: MATL 1/2" E.M.T. U.L. LISTED		DRAWING NO. HA-05-058	
FCR/ASST		 7051 VILLAGE DRIVE BUENA PARK, CA 90621-2200	
		TITLE: SAMPLING TUBES	