

## Specification

Part No.	LKV372EDID	
Technical	Transmitter-TX	Receiver-RX
HDMI compliance	1.4a	
HDCP compliance	1.2a	
Video bandwidth	225MHz(10.2Gbps)	
Video support	480I/P、576I/P、720P、1080I/P、3D	
Audio support	PCM、AC3、DTS	
InputTMDs signal	1.2Vp-p	
InputDDC signal	5V	
ESD protection	8KV	
EDID support	yes	
loop-out on TX	one HDMI loop-out on TX	
POE support	RX powered by TX	
IR passback	yes	
IR frequency Range (KHz)	20-60KHz	
Input	1xHDMI	1xRJ45, 1x3.5mm(IR)
Output	1xHDMI, 1xRJ45, 1x3.5mm(IR)	1xHDMI
HDMI connector	Type A, Female, 19-pin	
RJ-45 connector	RJ-45	
Mechanical	Transmitter-TX	Receiver-RX
Housing	Metal enclosure	
Dimensions(LxWxH mm)	71.6x66.6x22.6mm	71.6x66.6x22.6mm
Net weight	83g	83g
Fixedness	wall-mounting case with screws	
Power supply	5V2A	
Consumption	≤3W	≤3W
Operation temperature	0~40℃	
Storage temperature	-20~70℃	
Relative humidity	0~95%(non-condensing)	