

INDUSTRIAL

by AccessPRO

XT5000PRO Tripod Turnstile

The Industrial By AccessPRO XT5000PRO tripod turnstile series is a compact and cost-effective entrance control system designed for high-traffic volume.

XT5000PRO is a single-lane tripod turnstile series designed for smooth and silent operation and draws very little power. It's made of stainless steel which makes XT5000PRO highly durable. XT1000PRO Pro is also surprisingly compact and designed to operate in small workspaces.

XT5000PRO tripod arms are normally held in a locked position, thus denying access to the secured side. Upon XT5000PRO reader (RFID and/or fingerprint) positively recognizing a user's valid access card or fingerprint, its tripod arms unlock, thus allowing users passage to the secured side.

During emergencies and power outages the tripod arms completely collapse, thereby ensuring users FAST unencumbered exit to safety.

XT5000PRO provides both security and convenience, all in a very durable compact design.

Features



Reliability

- Alloy steel tripod hub and SUS304 stainless steel casework & tripod arms ensure long-lasting durability
- Power conservation. Electro-magnetic locks remain in "standby mode" until turnstile is activated
- Patented oil lubrication system reduces need for maintenance
- High quality electrical components



Safety Features

- Tripod-arms unlock & drop during emergencies/power loss
- Visual indicator for access granted (or denied)
- Ergonomic design makes card and fingerprint authentication fast & simple for users
- Secure. Supports Anti-tailgating



Built-in Reader Integration

- TS2000 Pro series ships already integrated with our customers' preference for either card or fingerprint access control reader. This greatly reduces installation time & expense
- TS2000 Pro series and associated access control readers are all factory-tested prior to shipping



XT5000PRO Series

INDUSTRIAL

by AccessPRO

Specifications

Power requirements	AC110V/220V, 50/60 Hz	
Power consumption	Starting	73 W
	Standby	20 W
	Unlock	63 W
Working temperature	-28 - 60 °C	
Working humidity	5 - 80%	
Working environment	Indoor/Outdoor(if sheltered)	
Speed of throughput	RFID	Maximum 30/minute
	Fingerprint	Maximum 25/minute
Lane width (mm)	505	
Footprint (mm*mm)	785*1110	
Dimension (mm)	L=1110, W=280, H=987	

Dimension with packing (mm)	L=1175, W=370, H=1070
Net weight (kg)	46
Weight with packing (kg)	54
LED indicator	Y
Cabinet material	SUS304 Stainless Steel
Lid material	SUS304 Stainless Steel
Barrier material	SUS304 Stainless Steel
Barrier movement	Rotating
Emergency mode	Y
Security level	Medium
MCBF	1 million
Options/Accessories	Counter, SUS316 Cabinet and Lid, Remote Control

Dimensions (mm)

